



## SYLVAC Digital Måletaster P12D 0-12,7 mmx0,01 um med M8 tilslutning (High Resolution- 801.1212)

### SYL8011212

- High-precision measuring probes with patented measuring system combining inductive and capacitive technologies
- Absolute system with integrated electronic error correction (no more pairing with the unit or computer) guaranteeing high accuracy over the entire measuring range
- Extremely robust ball bearing guide guarantees a minimum of 100 million cycles (30 millions with radial load)
- Stainless steel body Ø 12 mm, fixing diameter 8 h6
- Measuring range 12.7 mm
- Available in 3 versions: Standard, Work and Pro
- Measuring force selectable: low or very low for vertical use only
- Output signal in direct digital format without the need for a converter
- Reading speed up to 100 values per second depending on configuration
- Straight cable length 2m with either USB or M8 connector
- Cable outlet protected by a spring which can be tilted by 90° with the optional accessory 801-5101
- Protection class IP54

### Produktdetaljer

Varenr. SYL8011212

EAN

Toldtarif 90178000

Salgskvantum 1

### Produktspecifikationer

Barcode 7640125715552

Fejlgrænse 0,6 µm

Varemærke SYLVAC

Aflæsning 0,01 µm

Nøjagtighed 0,6 µm

SYLVAC varenr. 801-1212

Måleområde 0-12,7 mm

IP Klasse IP54

Data udgang M8

Gentagelsesnøjagtighed 0,08 µm

Model P12D HR M8

Brutto vægt 0,200 kg

Netto vægt 0,200 kg