



SYLVAC Digital Måleur S_Dial PRO SMART 25 x 0,0001 Ø 8mm IP51 (805.8502) BT - SPRING

SYL8058502

- Robust digital comparator with Ø 59.5 mm housing rotatable by 270°.
- Large display resolution 0.0001 mm (0.1 µm) with tolerance status indication by colour LEDs
- High accuracy over the entire measuring range thanks to an electronically corrected scale system with reference marks
- Measuring error less than 1.2 µm over 50 mm
- Three buttons, including the central button with selectable favourite function
- Wide range of functions, including MIN/MAX/DELTA
- Bluetooth®, Proximity» and «Power» data outputs allowing the instrument to be used without batteries when connected by this cable.
- Available with a fixing diameter of 8 mm and 25 mm for some models
- Measuring range of your choice: 25, 50 and 100 mm
- Available in standard pressure or low-pressure version without return spring for vertical use.
- Protection class IP51

Produktdetaljer

Varenr. SYL8058502

EAN

Toldtarif 90178000

Salgskvantum 1

Produktspecifikationer

Barcode 7640125029017

Fejlgrænse 1 µm

Produkt type Digital måleur

Varemærke SYLVAC

Aflæsning 0,0001 mm

Nøjagtighed 0,2 µm

SYLVAC varenr. 805-8502

Måleområde 0-25 mm

Batteri CR2032

IP Klasse IP51

Data udgang Bluetooth / USB / RS232

Gentagelsesnøjagtighed 0,2 µm

Diameter Ø59,5 mm

Skaft Ø8 h6

Brutto vægt 0,340 kg

Netto vægt 0,340 kg